



Arm and disarm with the push of a button

In addition to the smartphone and tablet option, the Smartvest Wireless Remote Control offers you another streamlined and convenient option for operation - at the push of a button, without the need for a PIN code. With this option, you can both arm and disarm the Smartvest or, in an emergency, trigger a panic alarm at the touch of a button. Using the app, the button can also be configured so that certain cameras or the siren are activated when the buttons are pressed. The Smartvest Wireless Remote Control thus provides basic control options in a compact and handy form ensuring it is simple and intuitive to use.

Remark:

The Smartvest Wireless Remote Control is protected against so-called replay attacks by an integrated security mechanism. All switching commands to the Smartvest alarm panel are individualized and thus not reproducible by unauthorized third parties.

Technologies

- Smartvest extension for operation without a mobile device
- Immediate operation at the push of a button and with no need for a PIN code
- Buttons for arming and disarming the Smartvest
- Panic alarm that can be triggered at the push of a button
- Individual configuration of buttons to automatically activate additional components (cameras, sirens, etc.) simultaneously
- Visual feedback via blue LED
- Low battery notification sent to the Smartvest alarm control panel
- Small, portable and easy to use
- Security-mechanism for protection against Replay-attacks

4003318774430



Security Tech Germany

Art.-Nr. FUBE35001A

Seite 2 von 2

Technical data - 4003318774430

| | |
|-----------------------------|--|
| Battery - battery operation | Yes |
| Battery - max. battery life | 2 y |
| Battery - quantity | 1 |
| Battery - type | CR2032 (3V) |
| Colour | White |
| Compatible with Secvest | No |
| Compatible with Smartvest | Yes |
| Dimensions | (B x L x H) 30 x 14 x 60 mm |
| Display | LED |
| Gross weight | 0,056 kg |
| Housing material | Plastic |
| Max. humidity | 80 % |
| Max. operating temperature | 40 °C |
| Min. humidity | 10 |
| Min. operating temperature | 0 °C |
| Net weight | 0,022 kg |
| Power consumption | 15 mA |
| Radio frequency | 868 MHz |
| Radio modulation | FSK |
| Standby power consumption | 0,005 mA |
| Transmission power | 4,5 dBm |
| Wireless range | (Depending on installation) 30 - 100 m |