



The Smartvest Wireless Motion Detector (pet immune) enables you to monitor rooms, while its battery operation makes it easy to install, avoiding the need for drilling and wiring. It reliably detects persons in the room using infrared, within a range of up to 12 metres. The integrated PET function omits pets of up to approx. 30kg from surveillance, in order to avoid false alarms as far as possible. When the battery is low, the Smartvest Wireless Motion Detector sends an automatic notification to the alarm panel. The free Smartvest app then guides you step by step through the process of replacing the batteries. In combination with the Smartvest Wireless Socket, you can then initiate certain smart functions such as “motion detected” or “socket on”, in addition to surveillance.

Technologies

- Smartvest extension for monitoring rooms
- Does not react to pets up to a weight of approx. 30 kg
- Quick and cable-free installation without the need for wires or drilling thanks to battery operation
- Detects people using infrared with a horizontal detection range of 110° and a maximum range of 10 m
- Visual feedback via red LED when starting up and in use
- Automatic supervision with functional tests repeated daily and feedback sent to the Smartvest alarm control panel
- Low battery notification sent to the Smartvest alarm control panel
- Battery life of up to 2 years
- Tamper protection via cover contact

Technical data - 4003318879111

| | |
|-----------------------------|-----------|
| Area of application | Inside |
| Battery - battery operation | Yes |
| Battery - max. battery life | 2 y |
| Battery - quantity | 3 |
| Battery - type | AA (1,5V) |

4003318879111



Security Tech Germany

Art.-Nr. FUBW35010A

Seite 2 von 2

Technical data - 4003318879111

| | |
|------------------------------|--|
| Colour | White |
| Compatible with Secvest | No |
| Compatible with Smartvest | Yes |
| Compatible with wAppLoxx | No |
| Dimensions | (B x L x H) 61 x 52 x 110 mm |
| Display | LED |
| Gross weight | 0,252 kg |
| Housing material | Plastic |
| Max. humidity | 80 % |
| Max. operating temperature | 40 °C |
| Min. humidity | 10 |
| Min. operating temperature | 0 °C |
| Net weight | 0,163 kg |
| PIR viewing angle horizontal | 110 ° |
| PIR viewing angle vertical | 45 ° |
| Pet-proof | Yes |
| Power consumption | 15 mA |
| Radio frequency | 868 MHz |
| Radio modulation | FSK |
| Sensor type | PIR |
| Standby power consumption | 0,03 mA |
| Tamper protection | No |
| Transmission power | 5,6 dBm |
| Type of detection | Heat detection |
| Wireless range | (Depending on installation) 30 - 100 m |