

# IP Panorama Dome 8 MPx (180°, WL)

Art.-Nr. IPCS28581A

Seite 1 von 3



## ONE CAMERA. 180° SURVEILLANCE

The multi-imager overview camera for your company premises: with 4K resolution, colour night vision and white light LEDs, the panoramic camera delivers crystal-clear images even in difficult lighting situations.

### 180° panoramic field of view

The surveillance camera composes a complete 180° panoramic image from the viewing angles of two camera modules. For the best overview without blind spots, also suitable for ultra widescreen display. The LAN camera can be swivelled downwards during installation to capture the area directly in front of/below the camera.

### Colour night vision & contrast

See what is happening in total darkness in high-contrast colour images. Even overexposed areas (e.g. with backlighting) are optimally displayed thanks to WDR contrast equalisation.

### Fully automatic: person/vehicle object detection

The security camera precisely distinguishes relevant objects (people, vehicles) from disruptive influences and reduces unnecessary motion alarms. For example, person detection triggers an alarm event (app, recorder, software, local alarm) and recording (memory card, ABUS recorder, VMS software).

### Alarm camera

Visible, loud alarm with flashing light and warning tone. Perpetrators can also be addressed acoustically via loudspeaker.

### ABUS Link Station app

Mobile access with live view, playback and push alarm.

# IP Panorama Dome 8 MPx (180°, WL)

Art.-Nr. IPCS28581A

Seite 2 von 3

## Technical data - IP Panorama Dome 8 MPx (180°, WL)

Aperture at minimum illumination (colour)	1.0
Audio	Integrated: Microphone, Loudspeaker; Connectable: Microphone, Loudspeaker
Backlight compensation	WDR, BLC, HLC
Camera type	Dome
Compatible with	NVR, ABUS Link Station App, ABUS CMS
Compatible with ABUS Link Station	Yes
DC voltage supply	12 (+/-25 %) V
Design	Dome
Diameter	155 mm
Digital zoom	Yes
Dimensions	(H x D) 155 x 155 mm mm
Dynamic range (WDR)	130 dB
Electronic shutter	1/3 - 1/50000 s
Encryption	HTTPS, TLS 1.2
Focal length	2 x 4 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20 fps
Gross weight	1,9 kg
Height	155 mm
Horizontal viewing angle	180 °
Housing material	Metal
IP protection class	67
Image sensor	2 x 1/1,8" Progressive Scan CMOS
Installation type	Ceiling, Wall
LAN network access	RJ45 10M/100M self-adaptive
Lens	Fix
Loudspeaker	Yes
Max. resolution @ frame rate	5120 x 1440 @ 20 fps
Microphone	Yes
Min. operating temperature	-30 °C
Minimum illumination (colour)	0,0005 lx
Motion detection	Yes
Net weight	1,1 kg
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ABUS Server, P2P, QoS, 802.1X, SNMP
Noise reduction	3D DNR
ONVIF	Profile G, S, T

# IP Panorama Dome 8 MPx (180°, WL)

Art.-Nr. IPCS28581A

Seite 3 von 3

## Technical data - IP Panorama Dome 8 MPx (180°, WL)

OSD language	DE, UK, FR, NL, DK, IT
Other functions	Object Classification Person/Vehicle
Pixels (effective)	5120(H) x 1440(V) pixel
PoE standard	IEEE 802.3af
Power consumption	900 mA
Private zones	No
Relay output	1
Resolution	8 MP
Resolution modes	WDR off: Stream 1: 5120 x 1440 @ 20 fps, Stream 2: 1920 x 536 @ 20 fps, WDR on: Stream 1: 5120 x 1440 @ 12.5 fps, Stream 2: 1920 x 536 @ 12.5 fps
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	MS Edge, IE11, Google Chrome
Technology	IP
Vertical viewing angle	44 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection, Region Entrance, Region Exit
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG
Video network bandwidth	32 kBit/s - 16 MBit/s
White balance	AWB, Manual
White-light LEDs	4
White-light range (up to)	30 m