

Art.-Nr. PPIC52520 Seite 1 von 4



Precise & clear. In 4K

This clever surveillance camera sends you accurate information, delivers ultra-sharp 4K recordings, and includes functions for intercom, alarm and much more

Some security cameras keep sending push notifications without taking into account whether the trigger is relevant to you. Instead of guessing, you should be able to rely on your surveillance camera. And in an emergency, it should provide clarity.

The SmartLook Pan & Tilt camera therefore distinguishes completely automatically between people, animals and vehicles. You decide what is important to you and only then will you receive a push message via the App2Cam Plus mobile phone app. This saves time and means you do not worry unnecessarily.

Another highlight: the camera delivers brilliant image quality day and night. It saves recordings in ultra-high resolution in 4K.

Incidentally, all functions are permanently available to you free of charge with the app: for example, to hide private and public areas and to turn the camera eye very quickly to a specific position. The same applies to access on the go and the intercom function so that you can talk to parcel couriers without contact, for example. With the included microSD memory card, the camera is immediately ready to record and the app even shows what happened up to 5 seconds before motion was detected (pre-recording).

The smart security camera is ready for immediate use after very simple set-up, is completely weatherproof and is therefore ideal for outdoor use. It has all you need for data protection-compliant operation. Compatible with the Smartvest wireless alarm system. Soon also with the ABUS One app: There you can access important camera functions and operate many other smart ABUS devices with just one app - clever, reliable, convenient.



Art.-Nr. PPIC52520 Seite 2 von 4

### **Technologies**

- Smart and weatherproof pan & tilt surveillance camera with free mobile phone app, recordings in 4K/UHD resolution, night vision, intelligent motion detection & push notification, intercom function and much more
- Ready to use immediately, no account/subscription required: integrated, exchangeable microSD memory card included
- Easy start-up in just a few minutes: with the App2Cam Plus app for smartphones/tablets & Bluetooth®
- Flexible outdoor placement: connected to your home network via Wi-Fi with high stability & range (2.4 or 5 GHz) or via LAN cable
- Fully automatic detection and differentiation of objects (people, animals, vehicles), then sends a targeted push message/email, ignores disturbances (branches, foliage, light, etc.)
- All functions permanently free of charge: live stream, digital zoom, 2-way audio through speakers & microphone, siren sound, memory, over-the-air updates and much more
- Customise all settings as required: motion detector sensitivity, image zones without detection, semi-automatic quick rotation via app to 3 definable positions (preset) etc.
- Data protection-compliant thanks to recording without sound, ring buffer and image areas blacked out as required (so-called privacy zones, also for public areas & neighbouring properties)
- Recordings in Ultra HD (8 megapixels), night vision up to 20 m, protection class IP66 (weatherproof)
- Compatible with the Smartvest app & soon also ABUS One

#### Technical data - SmartLook Pan & Tilt

Alarming	Push notification / E-Mail
Aperture	F2.0
Area of application	Outdoor use
Audio bitrate	16 Kbit/s
Audio compression	AAC
Audio input	Microphone
Audio output	Loudspeaker
Automatic aperture control	Yes
Base event	Object detection + motion mask
Channel width	20 MHz
Colour	white
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
DC voltage supply	5 V
Day/night switching	Auto
Design	PTZ
Dimensions	210 x 120 x 160 mm



Art.-Nr. PPIC52520 Seite 3 von 4

### Technical data - SmartLook Pan & Tilt

Focal length Frequency range  Z,400 – 2,485 / 5,0 GHz  Functions  Animal recognition, People recognition, Pan-tilt, Zoom, Night vision  Horizontal viewing angle  Housing material  IP protection class  66  IR LEDS  Yes  IR range (up to)  IR swivel filter  Yes  Image sensor  Loudspeaker  Max. humidity  90 %  Max. operating temperature  Max. resolution @ frame rate  4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps  Microphone  Yes  Min. humidity  20  Min. operating temperature  -10 °C  Minimum illumination (IR)  Network access  RJ-45 connector (10/100 Mbps)  Network protocols  Network protocols  TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets  3  Optical Wave Length  PSTI conformity given  Yes  Ves  Ves  Ves  Ves  Ves  Ves  Ves
Functions Animal recognition, People recognition, Pan-tilt, Zoom, Night vision Horizontal viewing angle 85 ° Housing material Plastic IP protection class 66 IR LEDS Yes IR range (up to) 20 m IR swivel filter Yes Image sensor 1/2.8" CMOS Loudspeaker Yes Max. humidity 90 % Max. operating temperature 50 °C Max. resolution @ frame rate 4k Ultra HD @ 15fps / Full HD (1080p) @ 15fps Microphone Yes Min. operating temperature -10 °C Minimum illumination (IR) 0 Ix Minimum illumination (IR) 0 Ix Minimum illumination (IR) Network access RJ-45 connector (10/100 Mbps) Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP Number of presets 3 Optical Wave Length 940 nm PSTI conformity given Yes
Horizontal viewing angle 85 ° Housing material Plastic IP protection class 66 IR LEDs Yes IR range (up to) 20 m IR swivel filter Yes Image sensor 1/2.8" CMOS Loudspeaker Yes Max. humidity 90 % Max. operating temperature 50 °C Max. resolution @ frame rate 4k Ultra HD @ 15fps / Full HD (1080p) @ 15fps Microphone Yes Min. humidity 20 Min. operating temperature -10 °C Minimum illumination (IR) 0 lx Minimum illumination (IR) Minimum illumination (IR) Network access RJ-45 connector (10/100 Mbps) Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP Number of presets 3 Number of users 3 Optical Wave Length 940 nm PSTI conformity given Yes
Housing material Plastic  IP protection class 66  IR LEDS Yes  IR range (up to) 20 m  IR swivel filter Yes  Image sensor 1/2.8" CMOS  Loudspeaker Yes  Max. humidity 90 %  Max. operating temperature 50 °C  Max. resolution @ frame rate 4k Ultra HD @ 15fps / Full HD (1080p) @ 15fps  Microphone Yes  Min. humidity 20  Min. operating temperature -10 °C  Minimum illumination (IR) 0 lx  Minimum illumination (IR)  Minimum illumination (IR)  Network access RJ-45 connector (10/100 Mbps)  Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets 3  Number of users 3  Optical Wave Length 940 nm  PSTI conformity given Yes
IP protection class 66 IR LEDs Yes IR range (up to) 20 m IR swivel filter Yes Image sensor 1/2.8" CMOS Loudspeaker Yes Max. humidity 90 % Max. operating temperature 50 °C Max. resolution @ frame rate 4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps Microphone Yes Min. humidity 20 Min. operating temperature -10 °C Minimum illumination (IR) 0 lx Minimum illumination (IR) 1 lx (colour) Network access RJ-45 connector (10/100 Mbps) Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP Number of presets 3 Number of users 3 Optical Wave Length 940 nm PSTI conformity given Yes
IR LEDs Yes IR range (up to) 20 m IR swivel filter Yes Image sensor 1/2.8" CMOS Loudspeaker Yes Max. humidity 90 % Max. operating temperature 50 °C Max. resolution @ frame rate 4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps Microphone Yes Min. humidity 20 Min. operating temperature -10 °C Minimum illumination (IR) 0 Ix Minimum illumination (IR) Minimum illumination (IR) Network access RJ-45 connector (10/100 Mbps) Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP Number of presets 3 Number of users 3 Optical Wave Length 940 nm PSTI conformity given Yes
IR range (up to)  IR swivel filter  Yes  Image sensor  1/2.8" CMOS  Loudspeaker  Yes  Max. humidity  90 %  Max. operating temperature  Microphone  Yes  Min. humidity  20  Min. operating temperature  -10 °C  Minimum illumination (IR)  Minimum illumination  (colour)  Network access  RJ-45 connector (10/100 Mbps)  Network protocols  TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets  3  Number of users  3  Optical Wave Length  940 nm  PSTI conformity given  Yes
IR swivel filter  Image sensor  Loudspeaker  Yes  Max. humidity  90 %  Max. operating temperature  Microphone  Yes  Min. humidity  20  Min. operating temperature  Minimum illumination (IR)  Minimum illumination  (colour)  Network access  RJ-45 connector (10/100 Mbps)  Network protocols  TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets  3  Number of users  3  Optical Wave Length  PSTI conformity given  Yes  Yes  1/2.8" (MOS  4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps  Full HD (1080p) @
Image sensor  Loudspeaker  Yes  Max. humidity  90 %  Max. operating temperature  Min. resolution @ frame rate  Min. humidity  Min. operating temperature  Min. operating temperature  Min. operating temperature  Min. operating temperature  -10 °C  Minimum illumination (IR)  Minimum illumination  (colour)  Network access  RJ-45 connector (10/100 Mbps)  Network protocols  TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets  Number of users  Optical Wave Length  940 nm  PSTI conformity given  Yes
Loudspeaker Yes  Max. humidity 90 %  Max. operating temperature 50 °C  Max. resolution @ frame rate 4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps  Microphone Yes  Min. humidity 20  Min. operating temperature -10 °C  Minimum illumination (IR) 0 Ix  Minimum illumination 1 Ix  (colour)  Network access RJ-45 connector (10/100 Mbps)  Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets 3  Number of users 3  Optical Wave Length 940 nm  PSTI conformity given Yes
Max. humidity 90 %  Max. operating temperature 50 °C  Max. resolution @ frame rate 4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps  Microphone Yes  Min. humidity 20  Min. operating temperature -10 °C  Minimum illumination (IR) 0 Ix  Minimum illumination 1 Ix  (colour)  Network access RJ-45 connector (10/100 Mbps)  Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets 3  Number of users 3  Optical Wave Length 940 nm  PSTI conformity given Yes
Max. operating temperature 50 °C  Max. resolution @ frame rate 4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps  Microphone Yes  Min. humidity 20  Min. operating temperature -10 °C  Minimum illumination (IR) 0 Ix  Minimum illumination 1 Ix  (colour)  Network access RJ-45 connector (10/100 Mbps)  Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets 3  Number of users 3  Optical Wave Length 940 nm  PSTI conformity given Yes
Max. resolution @ frame rate
Max. resolution @ frame rate
Min. humidity  Min. operating temperature  -10 °C  Minimum illumination (IR)  Minimum illumination  (colour)  Network access  RJ-45 connector (10/100 Mbps)  Network protocols  TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets  Number of users  Optical Wave Length  PSTI conformity given  Yes
Min. operating temperature -10 °C  Minimum illumination (IR) 0 Ix  Minimum illumination 1 Ix (colour)  Network access RJ-45 connector (10/100 Mbps)  Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets 3  Number of users 3  Optical Wave Length 940 nm  PSTI conformity given Yes
Minimum illumination (IR)  Minimum illumination (colour)  Network access  RJ-45 connector (10/100 Mbps)  Network protocols  TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets  Number of users  Optical Wave Length  PSTI conformity given  O lx  Colour  1 lx  Colour  ABP  NUMPSTI Conformity given  O lx  D lx  O
Minimum illumination (colour)  Network access RJ-45 connector (10/100 Mbps)  Network protocols TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets 3  Number of users 3  Optical Wave Length 940 nm  PSTI conformity given Yes
(colour)RJ-45 connector (10/100 Mbps)Network protocolsTCP/IP, UDP, SMTP, NTP, DHCP, ARPNumber of presets3Number of users3Optical Wave Length940 nmPSTI conformity givenYes
Network accessRJ-45 connector (10/100 Mbps)Network protocolsTCP/IP, UDP, SMTP, NTP, DHCP, ARPNumber of presets3Number of users3Optical Wave Length940 nmPSTI conformity givenYes
Network protocols  TCP/IP, UDP, SMTP, NTP, DHCP, ARP  Number of presets  Number of users  Optical Wave Length  PSTI conformity given  Yes
Number of presets     3       Number of users     3       Optical Wave Length     940 nm       PSTI conformity given     Yes
Number of users 3 Optical Wave Length 940 nm PSTI conformity given Yes
Optical Wave Length 940 nm PSTI conformity given Yes
PSTI conformity given Yes
DCTI conformative required Vec
PSTI conformity required Yes
Pan/tilt range 270° Horizontal / 80° Vertical
Plug type DC-plug: 3,5 x 1,35 mm
Power consumption 4 W
Power supply Power adapter
Pre/post alarm memory up to 5 sec.
Private zones 3
Product security updates at 2026-10-31
least until
Recording modes Manual / Motion detection
Resolution modes 4K Ultra HD / Full HD (1080p) / VGA (360p)
Sensitivity -90 dBm



Art.-Nr. PPIC52520 Seite 4 von 4

### Technical data - SmartLook Pan & Tilt

Simultaneous network access	3
Software	App: ABUS App2Cam Plus (Android/iOS)
Storage medium	Micro-SD (up to 128GB)
System	Wireless networking
Transmission power	11b: 17 +/- 1,5dBm / 11g: 14 +/- 1,5dBm / 11n: 12,5 +/- 1,5dBm
Vertical viewing angle	45 °
Video Content Analysis (VCA)	Human / Animal / Vehicle Detection
Video compression	H.264/ H.264+
WLAN network access	IEEE 802.11 b/g/n/ac/ax
White balance	AWB
Wireless range	10-30 metre, depending on local conditions m