



PRACTICAL HOLDER

With the bracket for the GRANIT™ Detecto XPlus 8077 and GRANIT™ Detecto XPlus 8077 2.0 disc brake locks, you can transport your lock conveniently and securely.

The bracket is simply attached to the frame tube. This is possible on round frame tubes with diameters of 12-28 mm and on square frame tubes with diameters of 12-18 mm - two frame tubes are required in each case.

In addition to the screw connection of the plastic bracket and the metal clamp with rubberised inner surface, the lock is fixed in place with a sturdy cable tie with a metal core. This means that the bracket always stays in place, even under high loads.

Operation and use

- For transporting the GRANIT™ Detecto XPlus 8077 and GRANIT™ Detecto XPlus 8077 2.0 disc brake locks
 - Attachment to round frame tubes with diameters of 12-28 mm or square frame tubes with diameters of 12-18 mm (two frame tubes required in each case)
 - Two screw sets of different lengths included in the scope of delivery
 - Attachment via plastic bracket and metal clamp with rubberised inner surface
 - In addition to the screw fastening, the lock bracket is fixed to the frame tube with a robust cable tie with metal core – for high stability even under high loads
-

Bracket SH8077



Security Tech Germany

Seite 2 von 2

Technical data - Bracket SH8077

Weight	400 g
EAN	4003318594748