

Comfion wireless wall button (alarm)

Art.-Nr. FUAT80100

Seite 1 von 2



Silent alarm or smart home automation

With the Comfion wireless wall button, the choice is yours! This innovative wireless panic button offers two different use cases, depending on requirements: The button can be used as a classic panic button for a silent alarm or as a button for home automation for greater convenience.

Panic button mode

Pressing the button for two or three seconds immediately triggers a panic alarm at the Comfion alarm panel. A vibration confirmation (optional) indicates that the alarm has been successfully transmitted. You can choose whether the alarm sounds loudly on site or whether a control centre should be informed inconspicuously - perfect for discreet emergencies. Thanks to this flexibility, the button is ideal for use in bedrooms or placed inconspicuously on the edge of a shop counter.

For more convenience

Alternatively, the button can be used to control automated functions. A previously defined automation can be triggered in the Comfion by simply pressing the button - ideal for smart control solutions in everyday life.

Certified security according to EN Grade 2

The device is certified to EN 50131 Grade 2, which guarantees maximum security and reliability in the event of an alarm. Thanks to its flexible mounting options, the button can be either glued or screwed into place, depending on the individual requirements of the surroundings.

This button not only impresses with its security functions, but also with its versatility in the field of home automation.

Technologies

Comfion wireless wall button (alarm)

Art.-Nr. FUAT80100

Seite 2 von 2

- Two operating modes: panic alarm or button for smart home automation
- Loud alarm or silent alarm option as required
- Vibration confirmation on alarm activation
- Certified to EN 50131 Grade 2 for maximum security
- Simple installation: screw or glue mounting

Technical data - Comfion wireless wall button (alarm)

Area of application	Interior
Battery - max. battery life	5 y
Battery - quantity	1
Battery - type	CR123A
Certifications	EN 50131 Grade 2
Colour	white
Compatible with	Comfion
DC voltage supply	3 V
Depth	21 mm
Dimensions	48 x 76 x 21 mm
EN	Level 2
Environmental class	II
Fuse protection type	Intrusion protection
Gross weight	0,06 kg
Height	76 mm
Max. humidity	95 %
Max. operating temperature	50 °C
Max. receiving range (free field)	1.000 m
Max. transmission range (free field)	1.000 m
Min. operating temperature	-20 °C
Modulation	2FSK
Net weight	0,042 kg
Radio frequency	868 MHz
Radio power	25 mW
Sabotage monitoring	Yes
Security level	2
Standard	EN50131-3:2009, EN50131-5-3:2017
Voltage monitoring	Yes
Width	48 mm