

# Universal bracket 300 mm

Art.-Nr. TVAC32130

Seite 1 von 2



## ELEGANT, VERSATILE, FAST: FOR THE PERFECT ASSEMBLY

Get your cameras in perfect position! With the elegant aluminium bracket, there are no limits to your installation wishes. Use the bracket as a table stand or for ceiling mounting, for example.

With the 1/4" (1/4 inch) thread of the tripod screw, the mount can be used universally for many different devices. In addition to surveillance cameras (box cameras, Boxtype, etc.) also for IR illuminators, photo cameras or equipment from laboratory and measurement technology, for example.

The universal camera holder is equipped with a 360° ball head with quick release. Its carrying capacity is 3 kg.

The internal cable routing provides protection from the weather.

Choose from the following camera mounts: Universal holder 160 mm (TVAC32120) and universal holder 300 mm (TVAC32130).

## Technologies

- Elegant aluminium holder, universally usable for mounting technical devices
- 360° ball head with quick-release fastener for easy attachment and optimal alignment of devices
- 1/4" stand screw (male) for units with 1/4" screw base (female)
- Versatile use, e.g. as a table stand, ceiling mount, etc.
- Suitable mount e.g. for security cameras (Boxtype), IR illuminators, photo cameras, laboratory and measuring equipment as well as other equipment in trade and industry
- Internal cable routing possible (weather protection)
- Length of stand tube: 300 mm (for ceiling mounting: distance from the ceiling)
- Load-bearing capacity: 3 kg

# Universal bracket 300 mm

Art.-Nr. TVAC32130

Seite 2 von 2

---

## Technical data - Universal bracket 300 mm

|                  |                    |
|------------------|--------------------|
| Alignment        | 360 °              |
| Cabling          | internal           |
| Colour           | Silver             |
| Connection type  | 1/4" tripod socket |
| Height           | 300 mm             |
| Housing material | aluminium          |
| Length           | 110 mm             |
| Load capacity    | 3 kg               |
| Width            | 110 mm             |