

4-Port PoE Gigabit Switch

Art.-Nr. ITAC10100

Seite 1 von 2



Technology for use in professional security surveillance systems.

The 4-Port PoE Gigabit Switch was specially developed for use in professional and high-resolution video surveillance systems and provides four gigabit downlink PoE ports and two gigabit uplink ports.

Use PoE instead of power supply unit.

Each downlink port delivers up to 30watts PoE output power. The switch is therefore highly suitable for directly operating ABUS IP cameras, which means that no additional power supply unit is required.

A total PoE output power of 60watts is available. For example, simultaneous operation is possible for up to:

Four PoE network devices

Two PoE+ network devices

Two PoE and one PoE+ network devices

Installation made easy.

The compact design and the mounting tabs provided make it quick and easy to install the switch in various locations.

Technologies

- Connections: 4 x PoE gigabit (downstream), 2 x gigabit (uplink)
- Supports PoE and PoE+
- Plug & Play, no configuration required
- Robust design, easy to install anywhere

Technical data - 4-Port PoE Gigabit Switch

DC voltage supply	48~57 V
Dimensions	(LxWxH) 135 x 86 x 27 mm
Height	27 mm
Length	135 mm
Max. PoE power per port	30 Watt
Max. humidity	95 %
Max. operating temperature	45 °C
Min. operating temperature	-10 °C
Net weight	0,343 kg
Network Standards	IEEE802.3 , IEEE802.3u, IEEE802.3ab, IEEE802.3 X
Network access	Downstream: 4x 10/100/1000Base-T (PoE), Uplink: 2x 10/100/1000Base-T

4-Port PoE Gigabit Switch

Art.-Nr. ITAC10100

Seite 2 von 2

Technical data - 4-Port PoE Gigabit Switch

PoE power total	60 Watt
PoE standard	802.3af/at (PSE)
Power Pin Assignment	1/2(+), 3/6(-)
Power consumption	5 W
Width	86 mm