

International plug-in power supply 12V/1.5A



Security Tech Germany

Art.-Nr. 505366

Seite 1 von 2



The international plug-in power supply unit supplies the WLX Repeater, WLX Pro Control Plus, WLX AE Control or TECTIQ access control center with the necessary voltage. The included international plug adapters enable international use in Europe, Great Britain and Australia.

Technologies

- Including adapter for EU, UK, AU
- Discreet design
- Power supply unit for WLX AE Control, WLX Repeater, WLX Pro Control Plus and TECTIQ access control center

Technical data - International plug-in power supply 12V/1.5A

AC voltage supply	100 – 240 V
DC voltage supply	12 V
Dimensions	44 × 74 × 35 mm
Gross weight	0,174 kg
Height	74 mm
Item abbreviation	NT-ST-12V
Length	35 mm
Net weight	0,174 kg
PSTI conformity required	No
Width	44 mm

Technical data - International Switching-Mode Power Supply 12 V/1.5 A (Cord)

AC voltage supply	100 – 240 V
Cable length	1,5 m
Dimensions	(W x H x D) about 44 x 74 x 35 mm
Height	74 mm
Housing material	ABS
Input voltage AC	230 V
Length	35 mm
Max. humidity	80 %

International plug-in power supply 12V/1.5A



Security Tech Germany

Art.-Nr. 505366

Seite 2 von 2

Technical data - International Switching-Mode Power Supply 12 V/1.5 A (Cord)

Max. operating temperature	40 °C
Min. operating temperature	0 °C
Net weight	0,153 kg
Output voltage DC	12 V
Width	44 mm
EAN	4043158146714